







Fasteners and Expansion Shields

ZINC IS STANDARD, STAINLESS STEEL MUST BE SPECIFIED
#10 SCREWS FOR EXTRUDED, #14 FOR CAST

BOTH EXTRUDED & CAST TREADS	Zinc Machine Screws Countersunk W/ Phillips Head #10-24 (¾" And 1¼" Lengths) or #14-24 (1½ Long) <i>Primary Use:</i> Bolt extruded treads to steel pan or concrete.	
	Stainless Steel Machine Screws Countersunk W/ Phillips Head #10-24 (¾" And 1¼" Lengths) or #14-24 (1½ Long) 18-8 Stainless Steel, <i>Primary Use:</i> Bolt extruded treads to steel pan or concrete in corrosive environments or marine applications.	
	#10-24 Hex Nut #10-24 or #14-24 Zinc or Stainless Steel available, use same type as screw. <i>Primary Use:</i> Bolt extruded treads to steel pan return or to secure wing anchors. Use with Stainless Steel Machine Screws.	
	Wing Anchor Mild Steel or Stainless Steel, 1½"L x ¾"W x ⅞"H <i>*Always include hex nuts on order, stainless steel must be specified</i> <i>Primary Use:</i> Cast products in new concrete. Attached to tread with machine screws & nuts.	
	Zinc Wood Screw Countersunk W/ Phillips Head #10 x 1½ or #14 x 1½ <i>Primary Use:</i> Extruded products on wood stairs	
	Stainless Steel Wood Screw Countersunk W/ Phillips Head #10 x 1½ or #14 x 1½, 18-8 Stainless Steel <i>Primary Use:</i> Extruded products on wood stairs in corrosive environments	
EXTRUDED ONLY	#10 Tapcon Screw Galvanized, Countersunk W/ Phillips Head 1¼" and 1¾" Lengths <i>Primary Use:</i> Extruded products to existing concrete or masonry.	
	#10 Expansion Shield <i>Primary Use:</i> Anchor tread to existing concrete or masonry, use with #10 machine screws.	
	#8-32 x ¾" Self-Tapping Zinc Machine Screw Countersunk W/ Phillips Head <i>Primary Use:</i> Attaches inserts to base <u>FOR 2-STAGE WOOD & INSERTS ONLY</u>	
CAST ONLY	Concealed Integral Anchor (Cast On Anchor) Aluminum. Approx. 1" long. <i>Primary Use:</i> Cast treads in new concrete. Only on types 100, 101, 101SP, 102, 103, 104, 105A, and 116 but MUST BE SPECIFIED. <u>FOR FOUNDRY USE ONLY!</u>	
	#14 x 1¾" Tapcon Screw Galvanized, Countersunk W/ Phillips Head <i>Primary Use:</i> Cast products to existing concrete or masonry. <u>FOR FOUNDRY USE ONLY!</u>	

ZINC IS STANDARD, STAINLESS STEEL MUST BE SPECIFIED
#10 SCREWS FOR EXTRUDED, #14 FOR CAST