

SAFE-STRIDE™

ACRYLIC, ABRASIVE ANTI-SLIP PAINT...

Provides anti-slip protection for most surfaces.

Safe-Stride is a newly improved and specially formulated anti-slip safety paint, which contains grit to help provide a tough, sure-footed, and safer-traction surface. Applied to cleaned bare materials such as wood, metal, asphalt, marble, concrete, stone, and many other surfaces; Safe-Stride will provide a durable and long wearing safety surface.



FEATURES

- Adheres to wood, concrete, primed metal
- Single coat application
- Easy water clean-up
- Apply with roller - preferred 1/4" nap
- Drying time - estimated 12 hours
- Coverage - estimated 100 sq. ft./gal.
- Lead, chromium, mercury free
- Available in special colors (over 100 gallons)

COLORS



Black



Gray



Safety Yellow

IMPORTANT NOTICE TO PURCHASER: THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE: Purchase or use of this product constitutes an agreement with Seller and Manufacturer that, if the product proves to be defective or in any way unsuitable, Seller's and Manufacturer's limit of liability for all damages, including but not limited to incidental or consequential damages, and User's or Purchaser's exclusive remedy, regardless of legal theory, including theories of breach of warranty, negligence and strict liability, shall be to receive at Seller's or Manufacturer's option, repair of the defective product, an equivalent quantity of replacement product or a refund of the purchase price.

TECHNICAL DATA

- Wt./Gal. - 12.5 lbs.
- No heavy metals
- Shelf life - 1 year unopened container
- Low VOC
- Applied as is from container
- Flat (textured) finish
- VOC - 0.14
- Priming surface is recommended but not required for good adhesion.

APPLICATION

Recommend priming of bare metal with a rust inhibitive primer. May be applied directly to properly aged, clean, sound concrete. Smooth, shiny concrete should be acid etched and thoroughly rinsed to promote adhesion. May be applied to bare or previously painted wood that is properly prepared. Do not apply if temperature will be below 50°F within 24 hours of painting or if rain is imminent. Avoid painting in direct sunlight.



WOOSTER PRODUCTS INC.

1000 Spruce Street, P.O. Box 6005, Wooster, Ohio 44691
Phone: (330) 264-2844 Call Toll Free: 1-800-321-4936 FAX: (330) 262-4151