



## TECHNICAL DATA SHEET

### **Safe-Stride Acrylic Anti-Slip Coating Application Instructions**

Safe-Stride coatings have been formulated for use on concrete, wood, and primed metal surfaces. When used properly, Safe-Stride products provide a tough, abrasive, anti-slip coating for walkways, steps, ramps, boat decks, locker room floors, and a variety of other uses.

#### SURFACE PREPARATION

To insure proper adhesion, all surfaces must be clean and free of dirt, grease, wax, mildew, rust, oil, chalk, and other foreign matter. Spalling or powdery concrete must be repaired to a sound surface before coating.

Concrete that is shiny smooth or suspected of treatment with chemical "de-icers" should be etched with diluted muriatic acid to promote bonding. Scuff sanding of glossy painted surfaces is recommended to secure the maximum adhesion of this product.

**CEMENT and MASONRY:** New concrete should age for at least thirty days prior to being top-coated. Bare and previously painted surfaces merely require preparation as described above before applying one or more coats of Safe-Stride Acrylic-Base.

**WOOD:** Bare or previously painted wood should be prepared as described above by removing any foreign matter, loose paint, or chalk, and scuff sanding painted glossy areas. Wolmanized wood must be aged a minimum of one year in order for product to adhere. One or two coats of Safe-Stride Acrylic-Base may be applied. Wood priming is not necessary when this product is used properly.

**METAL:** Any bare metal should be primed with any standard rust inhibiting metal primer following label directions before applying Safe-Stride Acrylic-Base.

#### APPLICATION

Stir thoroughly up on opening and remix periodically. Apply by brush, roller or trowel at a spreading rate of 100 to 125 sq. ft. per gallon. Thinning of this product is not recommended. When rolling, back brushing immediately after roller application is recommended for uniformity of the surface and durability of the product. Safe Stride Acrylic-Base is dry to walk on or recoat in 18 to 24 hours under normal drying conditions. The maximum hardness of this product is typically achieved in 7 to 14 days. All equipment should be cleaned immediately after use with soap and water and dried for storage.



**WOOSTER PRODUCTS INC.**  
1000 SPRUCE STREET • P.O. BOX 6005 • WOOSTER, OHIO 44691-6005

PHONE 330 / 264-2844  
1-800 / 321-4936  
FAX 330 / 262-4151

THE COMPLETE LINE OF  
SAFETY TREADS, THRESHOLDS  
& WALKWAY PRODUCTS

**GENERAL:** Safe-Stride Acrylic-Base anti-slip coatings are designed to reduce the hazards of slippery areas -not prevent these hazards. Do not paint if temperature will be below 50°F within twenty-four hours of application, or if rain is imminent. Do not paint in direct sunlight. This product is not recommended on garage floors on which cars will be parked or for underwater applications such as swimming pools. Cool or high temperatures will extend the drying time of this product.

**IMPORTANT NOTICE TO PURCHASER: THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

Purchase or use of this product constitutes an agreement with Seller and Manufacturer that, if the product proves to be defective or in any way unsuitable, Seller's and Manufacturer's limit of liability for all damages, including but not limited to incidental or consequential damages, and User's or Purchaser's exclusive remedy, regard less of legal theory, including theories of breach of warranty, negligence and strict liability, shall be to receive, at Seller's or Manufacturer's option, repair of the defective product, an equivalent quantity of replacement product or a refund of the purchase price.

**REFER TO SAFETY DATA SHEET FO FURTHER INFORMATION**

### **ADDITIONAL INFORMATION**

Wooster Products Inc.  
1000 Spruce Street  
Wooster, Ohio 44691  
Toll Free: 800-321-4936  
330-264-2844  
Fax: 330-263-0675  
Web-Site: <http://www.wooster-products.com>

### **NOTE**

While the information herein is currently believed to be accurate, we do not guarantee its 100% accuracy. Consumers, purchasers and end-users shall not solely rely on the statements herein when purchasing any Safe-Stride product. Consumers, purchasers and end-users should make every effort to perform their own investigations to determine if such products are suitable for their particular use and/or specific need. The products discussed are sold without warranty, expressed or implied, including a warranty of merchantability and fitness for use. Purchases will be subject to a separate agreement, which will not incorporate this document.

*Manufacturers of safety stair and walkway products*

Web Site: <http://www.wooster-products.com>

E-Mail: [Sales@wooster-products.com](mailto:Sales@wooster-products.com)