Printing Date 01/28/2022

Revision Date 01/28/2022

1 Identification

· Product Identifier

· Trade Name: Supergrit/Spectra Repair Kit Epoxy Based Part A (for all colors)

· Article number: 2049

· Relevant identified uses of the substance or mixture. Non-skid floor coating

Description: Part A of a two component solvent free non-skid epoxy mixture in various colors

· Details of the supplier of the safety data sheet

 $\cdot \ Manufacturer/Supplier:$

Wooster Products, Inc. 1000 Spruce Street Wooster, OH 44691

Phone Number: 1-800-321-4936/330-264-2844

 $\cdot \ Information \ department: \underline{sales@wooster-products.com}$

· Contact for the safety data sheet: Matt Gray

· Emergency telephone number: Chem-Trec: 1-800-424-9300

2. Hazards identification

· Classification of the substance or mixture



CHSOT



GHS09

- . Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms GHS07 Signal Word: Warning

GHS Hazard Class/Category	Code	Description
Skin Irrit. Category 2	H315	Causes skin irritation
Skin Sensitisation. Category 1	H317	May cause an allergic skin reaction
Eye Irrit. Category 2A	H319	Causes serious eye irritation
Toxic to Aquatic Environment Chronic Toxicity Category 2	H412	Harmful to aquatic life with long lasting effects

$\cdot \ Precautionary \ statements$

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

 $P261\ Avoid\ breathing\ dust/fume/gas/mist/vapors/spray.$

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303 IF ON SKIN:

P352 Wash with plenty of soap and water.

P333 If skin irritation or rash occurs:

P313 Get medical advice/attention.

P362 Take off contaminated clothing and wash before use.

(Contd. on page 2)

Printing Date 01/28/2022

Revision Date 01/28/2022

Trade Name: Supergrit/Spectra Repair Kit Epoxy Based Part A (for all colors)

(Contd. of page 1)

P304 IF INHALED:

P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 IF IN EYES:

P351 Rinse cautiously with water for several minutes.

P338 Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/federal regulations.

- · Classification system:
- · NFPA rating (scale 0 4)

Health = 2

Fire = 1

Reactivity = 0

· HMIS-rating (scale 0-4)

Health = 2

Flammability= 1

Physical hazards = 0

- Other hazards
- · PBT/vPvB: not applicable

Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Liquid Epoxy Mixture with dispersed solids

· Hazardous components:	CAS#	Weight %
Epoxy Resin	25068-38-6	10 - 15
Fused Aluminum Oxide	1344-28-1	20 - 25
Silica Sand	14808-60-7	60- 65
Pigments		<1

4 First-aid measures

· After Inhalation:

Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing and seek medical help immediately.

· After Skin Contact:

Immediately remove contaminated clothing or shoes, wipe excess from skin and flush with plenty of water at least 15 minutes. Use soap if available or follow washing with soap and water. Do not reuse clothing until thoroughly cleaned.

· After Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open and seek medical attention.

· After Ingestion:

Do not give any liquids (do not induce vomiting) if victim is unconscious or very drowsy. Get medical help immediately.

- · Information for doctor:
- . Most important symptoms and effects, both acute and delayed. No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

(Cont. on page 3)

Printing Date 01/28/2022 Revision Date 01/28/2022

Trade Name: Supergrit/Spectra Repair Kit Epoxy Based Part A (for all colors)

(Cont. of page 2)

5 Fire-fighting measures

- . Extinguishing media
- . Suitable extinguishing agents:

Use fire-fighting measures that suit the environment. Use dry chemical, CO₂, foam or water fog.

. Special fire-fighting procedures and precautions:

Full emergency equipment with self-contained breathing apparatus and full protective clothing should be worn by fire fighters.

Do not enter a confined space without full bunker gear, including a positive pressure NIOSH approved self-contained breathing apparatus.

During fire, irritating and toxic gases may be generated by thermal decomposition or combustion.

6 Accidental release measures

· Personal precautions protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Remove all sources of ignition and ventilate area. Dike and contain spilled material and control further spillage if feasible. Cover spill with liquid-binding material (clay, sand, sawdust, vermiculite, Fullers earth or other suitable absorbent). Collect material in non-leaking containers and seal tightly for disposal.

Dispose of contaminated material as waste in accordance with federal, state and local regulations.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information

7 Handling and storage

· Handling:

Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of the material from eyes, skin and clothing. Employee education and training in the safe use and handling of this material are required under the OSHA Hazard Communication Standard. Use with adequate ventilation.

· Storage

Store indoors in a cool dry location away from heat, sparks and flame.

- · Information about storage in one common storage facility: Store away from oxidizing agents.
- \cdot Further information about storage conditions:

Keep containers tightly closed when not in use.

8 Exposure controls/personal protection

- · Exposure controls
- · Personal protective equipment (see listings below)
- $\boldsymbol{\cdot}$ General protective and hygienic measures :

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

(Cont. on page 4)

Printing Date 01/28/2022 Revision Date 01/28/2022

Trade Name: Supergrit/Spectra Repair Kit Epoxy Based Part A (for all colors)

Contd. of page 3)

(Contd. on page 5)

· Respiratory protection:

Avoid breathing of vapors which may be produced under some conditions, such as heating.

· Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the produce/the substance/the preparation (examples: Nitrile rubber, NBR, Chloroprene rubber, CR).

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses with side shields.

Tightly sealed goggles or face shield.

• **Body protection:** Protective work clothing.

. TLV (Threshold limit value established by ACGIH		
Fused Aluminum Oxide	5 mg/m3 Respiratory Dust (TWA) → This limit applies to airborne, unbound particles of respirable size. Since aluminum oxide is dispersed in a liquid in our product these limits are only for information. Under normal storage and handling there should be no respirable aluminum oxide.	
Crystalline Silica	0.025 mg/m3 Respirable Fraction (TWA) → This applies to airborne, unbound particles of respirable size. Since silica sand is dispersed in a liquid in our product these limits are only for information. Under normal storage and handling there should be no respirable crystalline silica.	

9 Physical and chemical properties				
· Information on basic physical and chemical properties				
· General information				
· Appearance				
Form:	Liquid			
Color:	Various, product specific			
· Odor:	Characteristic			
· Odor threshold:	Not determined			
· pH-value:	Not determined			
· Change in condition				
· Melting point:	Not determined			
· Boiling point:	Not determined			
· Flash point:	> 200 ° F (PMCC)			
· Flammability limits:	UEL % Not established/ LEL % Not established			
· Auto ignition temperature:	Not determined			
· Decomposition temperature :	Not determined			
Note: These physical data are typical values based on material tested but may vary from sample to sample.				

Printing Date 01/28/2022 Revision Date 01/28/2022

Trade Name: Supergrit/Spectra Repair Kit Epoxy Based Part A (for all colors)

	(Contd. of page 4)
· Vapor density : · Evaporation rate :	Heavier than air Not determined
· Solubility in/Miscibility with Water:	Not miscible or difficult to mix.
· Solvent content : Organic solvents: VOC (Per EPA 24): Other information	0.0 % Not available GMS/L No further relevant information available.

10 Stability and reactivity

- . Chemical stability: Product is stable under normal conditions of storage and handling.
- . Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- . Possibility of hazardous reactions: Not reactive, as supplied.
- . Conditions to avoid: Exposures to high temperatures.
- . Incompatible materials: Reacts with oxidizing agents.
- . Materials to avoid: Lewis or mineral acids, organic bases such as primary and secondary aliphatic amines, oxidizing agents, curing agents-Considerable heat may be generated.
- . Hazardous decomposition products: By heat and fire: carbon monoxide and carbon dioxide, aldehydes and other organic substances may be formed
- . Hazardous polymerization: Hazardous polymerization will not occur under normal storage conditions. However, polymerization may occur over 500° F.

(Contd. on page 6)

Printing Date 01/28/2022 Revision Date 01/28/2022

Trade Name: Supergrit/Spectra Repair Kit Epoxy Based Part A (for all colors)

(Contd. of page 5)

11 Toxicological information

. Chronic Studies:

Recent 2 year bioassays in mice exposed by the dermal route to the diglycidyl ether of bisphenol A have yielded very limited evidence of weak carcinogenicity. The renal tumor evidence "was of no biological significance" and that the resin is not a systemic carcinogen when applied to the dorsal skin of CF1 mice". Based on this, the International Agency for Research on Cancer (IARC) concluded that DGEBPA was not classifiable as carcinogen (IARC Group 3) based on the following: Human and Animal Evidence – Inadequate.

DGEBPA have proved to be inactive when tested by in vivo mutagenicity assays. They have shown activity in vitro microbial mutagenicity screening tests and have produced chromosomal aberrations in cultured rat liver cells. The significance of this information to humans is unknown.

. Carcinogenic categories

. IARC (International Agency for Research on Cancer)

None of the ingredients listed

. NTP (National Toxicology Program)

None of the ingredients listed

12 Ecological information

- . Toxicity
- . Aquatic toxicity: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- . Persistence and degradability: No further relevant information available.
- . Behavior in environmental systems:
- . Bioaccumulative potential: No further relevant information available.
- . Mobility in soil: No further relevant information available.
- . Ecotoxical effects:
- . Remark: Toxic for fish.
- . Additional ecological information :
- . General notes: At present there is no ecotoxicological assessment.
- . Results of PBT and vPvB assessment
- . PBT: Not applicable.
- . VpvB: Not applicable.
- . Other adverse effects: No further relevant information available.

13 Disposal considerations

- . Waste treatment methods
- . Recommendation: Waste must be disposed of in accordance with federal, state, and local environmental control regulations. Incineration is the preferred method.
- . Uncleaned packagings:
- **. Recommendation:** Empty containers must be handled with care due to product residue. Disposal must be made according to official regulations. Do not heat or empty containers with electric or gas torch.
- . Controlled incineration or bury in legal landfill.

(Contd. on page 7)

Printing Date 01/28/2022 Revi

Revision Date 01/28/2022

Trade Name: Supergrit/Spectra Repair Kit Epoxy Based Part A (for all colors)

(Contd. of page 6)

14 Transport information

. US Ground (DOT)

Not regulated

- . Proper Shipping Name: Plastic liquid, Nos. (Not regulated by DOT) $\,$
- . Hazard Class or Division: None (Non Hazardous by DOT Regulation)
- . Packing Group: PG III. Hazard Label(s): None
- . Hazard Placard(s): None

. UN "model Regulation" ENVIRONMENTALLY HAZARDOUS

SUBSTANCE, LIQUID, N.O.S. (Epoxy resin), 9, III

UN3082

15 Regulatory information

. Safety, health and environmental regulations specific for the substance or mixture

- . SARA TITLE III
- . Section 355 (extremely hazardous substances):

None of the ingredients is listed.

- . SARA TITLE III
- Section 311/312 Hazard Categories:

Immediate (acute) health hazard. None of the ingredients is listed.

- . SARA TITLE III
- . Section 313 (Specific toxic chemical listings)

None of the ingredients is listed.

. TSCA (Toxic Substances Control Act)

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

- . Preposition 65: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm: Epichlorohydrin
- . RCRA: Under RCRA it is the responsibility of the product user to determine at the time of disposal whether a material containing the product or derived from the product should be classified as a hazardous waste. (40CFR 261.20-24)

(Contd. on page 8)

Printing Date 01/28/2022 Revision Date 01/28/2022

Trade Name: Supergrit/Spectra Repair Kit Epoxy Based Part A (for all colors)

(Contd. of page 7)

. Chemicals known to cause reproductive toxicity:

Epichlorohydrin

. (DSL) Canada Domestic Substance List

All components of this product are on the DSL (Canada Domestic Substance List) or are exempt from DSL.

. Carcinogenicity categories

. EPA (Environmental Protection Agency)

None of the ingredients listed

- . National regulations:
- . Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- . Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations contained in this SDS are presented in good faith and are believed to be correct as the date of this SDS, Wooster Products makes no representations as to the completeness or accuracy thereof. Final determination of suitability of any material is the sole responsibility of the user. In no event will Wooster Products or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

. Abbreviations and acronyms:

DOT: US Department of Transportation.

NFPA: National Fire Protection Association (USA). HMIS: Hazardous Materials Identification Systems.