



ABRASIVE CAST SAFETY THRESHOLDS

CAST THRESHOLDS PROVIDE:

Safe, anti slip walking surface.

FEATURES:

Maximum Durability in Rough Use
Indoor or Outdoor Use
Resistant to Corrosive Environment
New Construction or Renovation
Anti-slip Properties
Ready to Install Convenience

ABRASIVE CASTINGS SPECIFICATION:

- Provide Alumogrit® type **112**, size _____, thresholds as manufactured by Wooster Products Inc. for interior and exterior use.
- Abrasive shall be #20 virgin grain Aluminum Oxide (AL_2O_3) abrasive, integrally cast into the walking surface to a minimum depth of 1/32 inch.
- Cast metals used shall conform to the following specification:
 - Alumogrit® (Abrasive cast aluminum): No. 43 secondary ingot; low copper content; corrosion resistant.
- Any holes or countersinks shall be machine made. Screwheads shall not protrude above tread surface.
- All cast products shall have shot blasted finish.
- Cross hatching and fluting shall be 1/16 inch deep minimum and shall be clean and well defined.

STOP TYPE THRESHOLD

(50.8 mm for 101.6 mm, 12.7 mm widths)
2" for 4", 5" widths
2½" for 6" width
(63.5 mm for 152.4mm width)



TYPE 112

Standard widths 4", 5", & 6"
Height under door - 5/8"
Other widths and heights as required.
Plain abrasive surface

DRAWING NOT TO SCALE

FASTENERS: Thresholds are drilled and countersunk for 1/4" screws unless other fasteners are specified.

NOTCHING: Threshold ends can be factory notched for fast job site installation if frame details are furnished

LENGTHS: Lengths are to order up to 8'6" maximum in one piece. Lengths over maximum will be made in equal sections

WOOSTER PRODUCTS INC, 1000 SPRUCE ST., WOOSTER, OH 44691

Toll Free: 800-321-4936 Phone: 330-264-2844 Fax: 330-262-4151

Website: <http://www.wooster-products.com> E-mail: sales@wooster-products.com