



## ABRASIVE CAST SAFETY THRESHOLDS

### CAST THRESHOLDS PROVIDE:

Safe, anti slip walking surface.


### FEATURES:

- Maximum Durability in Rough Use
- Indoor or Outdoor Use
- Resistant to Corrosive Environment
- New Construction or Renovation
- Anti-slip Properties
- Ready to Install Convenience

### ABRASIVE CASTINGS SPECIFICATION:

- Provide Alumogrit® type **115**, size\_\_\_\_, thresholds as manufactured by Wooster Products Inc. for interior and exterior use.
- Abrasive shall be #20 virgin grain Aluminum Oxide ( $AL_2O_3$ ) abrasive, integrally cast into the walking surface to a minimum depth of 1/32 inch.
- Cast metals used shall conform to the following specification:  
Alumogrit® (Abrasive cast aluminum): No. 43 secondary ingot; low copper content; corrosion resistant.
- Any holes or countersinks shall be machine made. Screwheads shall not protrude above tread surface.
- All cast products shall have shot blasted finish.
- Cross hatching and fluting shall be 1/16 inch deep minimum and shall be clean and well defined.

### SADDLE TYPE THRESHOLD



#### TYPE 115

Standard widths 4", 5", & 6"  
Standard height - 1/2"  
Other widths and heights as required.  
Fluted abrasive surface.

DRAWING NOT TO SCALE

**FASTENERS:** Thresholds are drilled and countersunk for 1/4" screws unless other fasteners are specified.

**NOTCHING:** Threshold ends can be factory notched for fast job site installation if frame details are furnished

**LENGTHS:** Lengths are to order up to 8'6" maximum in one piece. Lengths over maximum will be made in equal sections

**WOOSTER PRODUCTS INC, 1000 SPRUCE ST., WOOSTER, OH 44691**

**Toll Free: 800-321-4936 Phone: 330-264-2844 Fax: 330-262-4151**

**Website: <http://www.wooster-products.com>**

**E-mail: [sales@wooster-products.com](mailto:sales@wooster-products.com)**